

COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR									
1	Manufacturer:	Chicago Pneumatic							
	Model Number:	CPVSd 20 15kW		Date:	08/16/23				
2	X Air-coole	d Water-cooled		Type:	Screw				
				# of Stages:	1				
3*	Full Load Operating Pressure		145	psig b					
4	Drive Motor Nominal Rating		20	hp					
5	Drive Motor Nominal Efficiency		91.0	percent					
6	Fan Motor Nominal Rating (if applicable)		0.45	hp					
7	Fan Motor Nomin	al Efficiency	32.0	percent					
8*	Input Power (kW)		Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d					
	16.3		66	24.90					
	12.4		51	24.50					
	9.3		35	27.20					
	8.7		32	27.70					
	5.4		15	35.40					
9*	Total Package Inp	ut Power at Zero Flow c, d	0.0	kW					
10	Isentropic Efficier	ncy	65.4	%					
11	Specific Power (RW/100 ACPN)	15.00 15.00 10.00 10.00 10.00 10.00 10.00	30 40 50	60 70	80				
		Note: Graph is only Note: Y-Axis Scale, 10 to	Capacity (ACFM) a visual representation of the data in 33, + 5kW/100acfm increments if neces ale, 0 to 25% over maximum capacity	Section 8	80				

^{*}For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
- a. Measured at the discharge terminal point of the compressor package in accordance with 15O 1217, Annex E, ACFM is actual cubic feet per minute at inlet conditions.

 b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.

 c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.

 d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
$\underline{m}^3 / \underline{min}$	ft ³ / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data