

## COMPRESSOR DATA SHEET

## In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR									
1	Manufacturer:	Chica	go Pneumatic						
	Model Number:	CPVS	d 20 15kW		Date: 08/10		/16/23		
2	X Air-cooled Water-cooled			Туре:		S	crew		
				# of Stages:			1		
3*	Full Load Operating Pressure			180	psig				
4	Drive Motor Nominal Rating			20	hp				
5	Drive Motor Nominal Efficiency			91.0		percent			
6	Fan Motor Nominal Rating (if applicable)			0.45	hp				
7	Fan Motor Nom	inal Efficie	ncy	32.0					
	Input Power (kW)		Capacity (acfm) <sup>a,d</sup>		Specific Power (kW/100 acfm) <sup>d</sup>				
8*	13.8			49	28.20		/		
	11.5			39		29.30			
	10.4			34		30.90			
	9.8			31		32.00			
	7.0			19		37.60			
9*	Total Package Input Power at Zero Flow c, d			0.0		kW			
10	Isentropic Effic	Isentropic Efficiency				%			
11	Specific Power (kWi100 ACFM)	35.00 30.00 25.00 20.00 15.00	Note: Graph is only a vi Note: Y-Axis Scale, 10 to 35,	30 40  Capacity (ACFM)  sual representation of the data in +5kW100acfm increments if nece to 25% over maximum capacity to 25% over maximum capacity	50 Section 8 Ssary above 35	60	- - - -		

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
- a. Measured at the discharge terminal point of the compressor package in accordance with 15O 1217, Annex E, ACFM is actual cubic feet per minute at inlet conditions.

  b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.

  c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.

  d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
$\underline{m}^3 / \underline{min}$	ft <sup>3</sup> / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data