

COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Frequency Drive

		MO	DEL D	ATA -	FOR (COMPI	RESSE	D AIR				
1	Manufacturer:	Chica	igo Pneu	ımatic								
	Model Number:	CPVS	Sd 29 22	kW				D	ate:	0	8/16/23	
2	X Air-cooled Water-cooled					7			/pe:	Screw		
								# of Stag	ges:		1	
3*	Full Load Opera	ating Pressu	ıre ^b	re					psig b			
4	Drive Motor Nominal Rating					30		hp				
5	Drive Motor Nominal Efficiency					92.4	1	percent				
6	Fan Motor Nominal Rating (if applicable)					0.43	3	hp				
7	Fan Motor Nom	inal Efficie	ency			35.0)		percent			
8*	Input Power			Ca	Capacity (acfm) ^{a,d}			Specific Power (kW/100 acfm) ^d				
	30.4					140			21.70			
	21.8				106			20.50				
	17.5					86			20.	30		
	11.7					58			20.30			
	6.4				,	29			22.	00		
9*	Total Package Input Power at Zero Flow c, d				1	0.0		kW			kW	
10	Isentropic Efficiency				62.00				%			
11	Specific Power (kW)100 ACFM)	35.00 30.00 25.00 20.00 15.00	20	40	60	. 80	100	120	140	160	— — — — — — — — — — — — — — — — — — —	
				s Scale, 10 to	a visual rep	00acfm incre		Section 8 essary above 35	;			

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
- a. Measured at the discharge terminal point of the compressor package in accordance with 15O 1217, Annex E, ACFM is actual cubic feet per minute at inlet conditions.

 b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.

 c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.

 d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

	blume Flow Rate pecified conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ / min	ft ³ / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data