

# WEDA pumps

Weda Dewatering pumps have evolved from a long history of improvements and are designed to be portable, easy, reliable and efficient. They cater to a wide range of dewatering applications from mines, process water, municipal and general dewatering. Low weight and high performance becomes a game changer when you have to move pumps to multiple locations. This is where Weda pumps make the difference and become a preferred choice of customers. The modular design helps in servicing the pump with ease. With the inbuilt electrical protections inside a sealed unit, installing the pump is a matter of minutes. These small things make a difference when you have to be quick and flexible in the field.



		WEDA 10		WEDA 30		WEDA 40	WEDA 50+		WEDA 60+		
		Single phase	Three phase	Single phase	Three phase	Three phase	Normal head	High head	Normal head	High head	Super high head
<b>Performance data</b>											
<b>Specifications</b>											
Max. head	ft	52	52	90	83	72	83	135	100	170	250
Max. flow	US gpm	117	119	200	190	450	620	310	700	340	260
Rated output	hp	1.5	1.3	2.7	2.5	4.0	8.5	8.5	11.5	11.5	11.5
	kW	1.1	1.0	2.0	1.9	3.0	6.3	6.3	8.6	8.6	8.6
Max. power input	kW	1.5	1.2	3.0	2.6	4.0	7.5	7.5	10.0	10.0	10.0
Rated current (115V)	A	13.5	-	-	-	-	-	-	-	-	-
Rated current (230V)	A	6.1	3.6	13.0	7.7	6.7	21.2	21.2	28.9	28.9	28.9
Rated current (460V)	A	-	1.8	-	3.9	5.8	10.6	10.6	14.5	14.5	14.5
Shaft speed	rpm	3550	3550	3550	3550	3550	3460	3460	3470	3470	3470
Discharge connection	in	2"	2"	3" (4")	3" (4")	3" (4")	4" (3")	3" (4")	4" (3")	3" (4")	3" (4")
Max solid handling size	in	0.16	0.16	0.27	0.27	0.27	0.32	0.32	0.32	0.32	0.32
<b>Weight and dimensions</b>											
Weight	lbs	27.5	27.5	44.0	44.0	55.0	122.0	122.0	134.0	134.0	138.0
Length	in	17.4	14.6	19.8	18.7	18.7	28.3	28.3	29.9	29.9	29.9
Width	in	8.70	8.70	11.2	11.2	11.2	13.0	11.9	13.0	11.9	11.9
Diameter	in	7.2	7.2	8.7	8.7	8.7	10.9	10.9	10.9	10.9	10.9