



Portable Diesel Compressors

Built for reliable
performance



People. Passion. Performance.

 Chicago
Pneumatic



Construction
Professional

Solutions **where and when** **you need them**


Chicago Pneumatic has built a real game changing line up when it comes to delivering on-site, air, power and light. Building on over 120 years of knowledge, our latest portfolio is our most innovative and toughest to date. The word toughness optimizes the Chicago Pneumatic brand. You will see toughness, coupled with superior portability and efficiency across the entire range.



ction
nal

ORIGINAL PART
1636 9778 00
1636 9778 00
1636 9778 00

ORIGINAL PART
1636 9778 00
1636 9778 00
1636 9778 00



THE
NEWS



2.0



Red Rock Range

Portable, powerful and tough



Stage V compliant

Xc2003 controller with dual pressure functionality

Red Rock polyethylene canopy

Easy service guarantee with all parts easily accessible

Spillage free frame

Low noise level according to European noise legislation

Robust and highly efficient mechanical engine from Kubota

Lifting beam



Portable

Most of the models can be towed behind a normal passenger car with no special driving license needed.



Powerful

Power up to two breakers with effortless ease. You can also get a generator included in the package if you wish.



Tough

The Red Rock canopy is made from extra tough polyethylene, protecting the working parts and ensuring your compressor looks and performs to its maximum, day in and day out.



		CPS 2.0-7	CPS 2.5-7	CPS 3.0-7	CPS 3.5-10	CPS 3.5-12
Normal effective working pressure	bar	7	7	7	10.3	7 12
	psi	100	100	100	150	100 150
Free air delivery	cfm	70	90	106	125	125 115
	m³/min	2.0	2.5	3.0	3.5	3.5 3.25
	l/s	33	42	50	58.9	58.6 54.4
Output power	kVA	-	-	-	-	-
Sound pressure level (LpA) at 7m	dB(A)	69	70	67	70	70
Sound power level (LwA)	dB(A)	97	98	95	98	98
Max. Ambient temperature at sea level	°C	50	47	50	50	50
Min. Starting temperature	°C	-10	-10	-10	-10	-10
Min. Starting temperature (Cold start aid)	°C	-20	-20	-20	-20	-20

Engine

Model		Kubota D 722	Kubota D 902	Kubota D 1105	Kubota V 1505-CR-T	Kubota V 1505-CR-T
Emission stage		Stage V	Stage V	Stage V	Stage V	Stage V
Number of cylinders		3	3	3	4	4
Power output @ normal shaft speed	kW	14.9	18.5	18.5	33	33
Full load RPM	rpm	3400	3400	3000	3000	3000
Unload RPM	rpm	2000	2000	1500	1800	1800

Capacity

Engine oil	l	3.8	3.8	4.5	8.5	8.5
Compressor oil	l	6	6	8	8	8
Fuel tank	l	28.5	28.5	45	45	45

Box unit dimensions

Length	mm	1570	1570	1940	1940	1940
Width	mm	1060	1060	1180	1180	1180
Height	mm	990	990	1150	1150	1150
Weight	kg	440	440	650	650	650

Undercarriage dimensions

Type	Trailer mounted with adjustable towbar (without brakes)					
Length	mm	1960	1960	2290	2290	2290
Width	mm	1230	1230	1350	1350	1350
Height	mm	1250	1250	1400	1400	1400
Weight	kg	600	600	749	749	749

		With Generator					
		CPS 5.0-7	CPS 5.0-10	CPS 2.5-7 G	CPS 3.0-7 G	CPS 3.5-7 G	CPS 5.0-7 G
Normal effective working pressure	bar	7	7 10.3	7	7	7	7
	psi	100	100 150	100	100	100	100
Free air delivery	cfm	174	174 120	90	106	125	174
	m³/min	5.0	5.0 3.5	2.5	3.0	3.5	5.0
	l/s	82	82 56.3	42	50	58	82
Output power	kVA	-	-	12	6 6.5	6 12	6.5 9
Sound pressure level (LpA) at 7m	dB(A)	70	70	70	67	70	70
Sound power level (LwA)	dB(A)	98	98	98	95	98	98
Max. Ambient temperature at sea level	°C	50	50	50	50	50	50
Min. Starting temperature	°C	-10	-10	-10	-10	-10	-10
Min. Starting temperature (Cold start aid)	°C	-20	-20	-20	-20	-20	-20

Engine

Model		Kubota V 1505-CR-T	Kubota V 1505-CR-T	Kubota V 1505-CR-T	Kubota D 1105	Kubota V 1505-CR-T	Kubota V 1505-CR-T
Emission stage		Stage V	Stage V	Stage V	Stage V	Stage V	Stage V
Number of cylinders		4	4	4	3	4	4
Power output @ normal shaft speed	kW	33	33	33	18.5	33	33
Full load RPM	rpm	3000	3000	3000	3000	3000	3000
Unload RPM	rpm	1800	1800	1800	1500	1800	1800

Capacity

Engine oil	l	8.5	8.5	8.5	4.5	8.5	8.5
Compressor oil	l	8	8	8	8	8	8
Fuel tank	l	60	60	60	60	60	60

Box unit dimensions

Length	mm	1940	1940	1940	1940	1940	1940
Width	mm	1180	1180	1180	1180	1180	1180
Height	mm	1150	1150	1150	1150	1150	1150
Weight	kg	650	650	650	650	650	650

Undercarriage dimensions

Type	Trailer mounted with adjustable towbar (without brakes)			Trailer mounted with adjustable towbar (without brakes)		
Length	mm	2290	2290	2290	2290	2290
Width	mm	1350	1350	1350	1350	1350
Height	mm	1400	1400	1400	1400	1400
Weight	kg	749	749	850	749	850

The dual pressure range

This range features our toughest mid-size compressors to date, designed to ease your work and enjoy the benefits of two machines in one package. The Dual Pressure Range works at flows between 5.5-7.0 m³/min and 9.8-11.5 m³/min. Depending on the application you are working on, you can either switch working pressure at between 7-10 bar or 12-14 bar, depending on the model chosen. The Red Rock canopy makes sure your compressor can withstand the harshest working conditions.

CPS 11.0-10 and CPS 11.0-14 features:

- Flows from 9,8-11,5 m³/min
- John Deere performance engine
- Red Rock canopy
- Lightweight and compact
- Intuitive user friendly control panel
- Corrosion free frame
- Compressor oil service interval of 1000 hours or once in every two years.
- All components are easy to access for simple service



CPS 7.0-10 features:

- Flows from 5,5-7,0 m³/min
- Kubota performance engine
- SPF frame
- Spin on vessel
- Red Rock canopy
- Intuitive use friendly controller

RED ROCK

		CPS 7.0-10	CPS 11.0-10	CPS 11.0-14
Normal effective working pressure (fixed presets)	bar (g)	7 10	7 10	7 14
	psi (g)	100 150	100 150	100 205
Free air delivery	cfm	250 189	405 345	385 360
	m ³ /min	7,0 5,5	11,5 9,8	11 10,2
	l/s	117 89	190 163	183 170
Max. Ambient temperature at sea level	°C	45	50	50
Min. Starting temperature	°C	-10	-10	-10
Min. Starting temperature (Cold start aid)	°C	-20	-25	-25

Engine

Model		Kubota V2403	John Deere 4045HFC04	John Deere 4045HFC04
Number of cylinders		4	4	4
Power output @ normal shaft speed	kW	47,9	86	104
Full load RPM	rpm	2700 2200	1900 2200	1950 2200
Unload RPM	rpm	1800	1500	1500

Capacity

Engine oil	l	9,5	14,7	14,7
Compressor oil	l	11	26,5	26,5
Fuel tank	l	87	168	168

Box unit dimensions

Length	mm	2138	2942	2942
Width	mm	1255	1490	1490
Height	mm	1184	1510	1510
Weight	kg	1100	2065	2065

Undercarriage dimensions

Length	mm	3747	4940	4940
Width	mm	1593	1580	1580
Height	mm	1572	1800	1800
Weight	kg	1300	2340	2340



SERVICE MADE EASY.

Easy access to change all parts.
Service kits to keep you **running**.

We have one simple goal – to keep you running. Chicago Pneumatic focusses on ease of doing business and reducing service time; quick access to parts is paramount to that promise. Our global network has all the parts, lubricants and accessories you need, ensuring we keep your product in tip-top condition and delivering exactly what you need it to deliver.

People. Passion. Performance.

Construction equipment portfolio

Air compressors



- Small air**
- 2-5 m³/min
 - 5.5-12 bar



- Medium air**
- 7-26 m³/min
 - 7-17 bar



- Large air**
- 16-51 m³/min
 - 7-28 bar

Handheld tools



- Pneumatic tools**
- Breakers (13.5-43.5 kg)
 - Hammers (4.3-15.4 kg)
 - Rock drills (14.7-29.5 kg)
 - Additional air tools



- Hydraulic tools**
- Hammers and Breaker (12-39 kg)
 - Power packs
 - Additional hydraulic tools



- Motor driven tools**
- Breakers (22.5 kg)
 - Motor drills (25 kg)
 - Tie tampers (22.5 kg)

Generators



- Mobile
- Stationary
- Portable

Light towers



- Diesel LED and MH
- Electric LED

Dewatering pumps



- Surface
- Submersible
- Small package

For more information, please contact your CP partner:

Use only authorized parts. Any damage or malfunction caused by the use of unauthorized parts is not covered by Warranty or Product Liability.