



Chicago Pneumatic



People.
Passion.
Performance.

CPPG Portable Generators (60 Hz)

The CPPG Inverter

The day-to-day silent solution below 3kVA. When it comes to fuel efficiency, compactness and noise attenuation, CPPG Inverter are the future. The variable speed smart control, together with paralleling capability, delivers efficient power with the lowest fuel consumption, adapting engine speed to the load conditions.



TECHNICAL DATA		CPPG INVERTER	
		CPPG2iW	CPPG3iW
Generator data			
Rated frequency	Hz	60	60
Rated voltage	V	120	120
Nominal power output	kVA	1,6	3,0
Peak power output	kVA	1,8	3,3
Power factor cos Phi		1	1
Fuel tank capacity	l	4	10
Fuel autonomy at nominal power	h	5	6
Sockets configuration		2 x 3P20A	2 x 3P20A + 1 x 3P30A
3P20A: Nema 120 V 20 A 3P30A: Nema 120 V 30A Twist Lock			
Engine			
Model		CP148F Gasoline	CP170FD Gasoline
Nominal speed	rpm	5000	3600
Power output	kWm	2,4	4,4
Displacement	cm3	79	212
Starter type		Recoil	Electric / Recoil
Exhaust gas compliant		EPA Tier 2	EPA Tier 2
Alternator			
Power	kVA	2	3
Noise level			
Sound pressure level (LpA) at 7m	dB(A)	65	63
Sound power level (LwA)	dB(A)	90	88
Weight and dimensions			
Length	mm	500	580
Width	mm	285	440
Height	mm	455	510
Weight	kg	21	45

The CPPG Standard

The CPPG Standard Line offers straight forward gasoline generators with all the features you need for your occasional use built right in. They are designed to deliver stable electrical output and safe, user-friendly operation over a long service life.



TECHNICAL DATA		CPPG STANDARD		
		CPPG2.5W	CPPG5.5W	CPPG7W
Generator data				
Rated frequency	Hz	60	60	60
Rated voltage	V	240 / 120	240 / 120	240 / 120
Nominal power output	kVA	2,5	5	6,5
Peak power output	kVA	2,8	5,5	7,0
Power factor cos Phi		1	1	1
Fuel tank capacity	l	15	25	25
Fuel autonomy at nominal power	h	11	10	8
Sockets configuration		2 x 3P20A + 1 x TL240	4 x 3P20A + 1 x TL240	4 x 3P20A + 1 x TL240
3P20A: Nema 120 V 20A TL240: Nema 240/120 V Twist Lock				
Engine				
Model		CP200FA Gasoline	CP390FD Gasoline	CP420FD Gasoline
Nominal speed	rpm	3600	3600	3600
Power output	kWm	4,1	8,2	9
Displacement	cm3	196	389	420
Starter type		Recoil	Electric / Recoil	Electric / Recoil
Exhaust gas compliant		EPA Tier 2	EPA Tier 2	EPA Tier 2
Alternator				
Power	kVA	2,5	5,5	6,5
Noise level				
Sound pressure level (LpA) at 7m	dB(A)	70	72	76
Sound power level (LwA)	dB(A)	95	97	101
Weight and dimensions				
Length	mm	590	675	680
Width	mm	430	540	550
Height	mm	480	540	550
Weight	kg	52	79	83



For more information, please contact your CP partner:

Use only authorized parts. Any damage or malfunction caused by the use of unauthorized parts is not covered by Warranty or Product Liability.